

Specifications

Lights

Headlights	High	12 V — 65 W (HB3) 12 V — 60 W (HB3)
	Low	12 V — 55 W (HB4) 12 V — 51 W (HB4)
Front turn signal lights		12 V — 21 W
Front parking lights		12 V — 5 W
Rear turn signal lights		12 V — 21 W
Stop/Taillights (and Rear side marker lights)		12 V — 21/5 W (3 CP)
Taillight		12 V — 3 CP
High-mount brake light		12 V — 21 W
Front side marker lights		12 V — 5 W
Back-up lights		12 V — 21 W
License plate lights		12 V — 3 CP
Ceiling light		12 V — 8 W
Trunk lights		12 V — 3.4 W
Door courtesy lights		12 V — 3.4 W
Vanity mirror light		12 V — 1.8 W

Battery

Capacity	12 V — 55 AH/5 HR
	12 V — 65 AH/20 HR

Fuses

Interior	See page 253 or the fuse label attached to the inside of the fuse box door under the dashboard.
Under-hood	See page 252 or the fuse box cover.

Engine

Type	Water cooled 4-stroke SOHC, SOHC VTEC 4-cylinder, SOHC 6-cylinder (V6), gasoline engine
Bore x Stroke	85.0 x 95.0 mm (3.35 x 3.74 in) 87.0 x 75.0 mm (3.43 x 2.95 in) *
Displacement	2,156 cm ³ (132 cu-in) 2,675 cm ³ (163.2 cu-in) *
Compression ratio	8.8 : 1 9.0 : 1 *
Spark plugs	See spark plug maintenance section pages 194 and 196 .

* : 6 cylinder models

Alignment

Toe-in	Front	0.0 mm (0.00 in)
	Rear	2.0 mm (0.08 in)
Camber	Front	0°
	Rear	-0°25'
Caster	Front	3°00'

CONTINUED

Specifications

Tires

Size	Front/Rear	P185/70R14 87S * ¹ 185/65R15 88S * ² 195/60R15 88H * ³ 205/60R15 91V * ⁴
	Spare	T115/70D14 * ⁵ T125/70D15 * ⁶ T135/90D15 * ⁴
Pressure	Front	220 kPa (2.2 kgf/cm ² , 32 psi)
	Rear	220 kPa (2.2 kgf/cm ² , 32 psi)
		200 kPa (2.0 kgf/cm ² , 29 psi) * ⁴
	Spare	420 kPa (4.2 kgf/cm ² , 60 psi)

*1 : U.S.: DX, Canada: LX

*2 : U.S.: LX, Special Edition, Canada: EX, Special Edition

*3 : U.S.: EX, Canada: EX-R

*4 : 6 cylinder models

*5 : U.S.: DX and LX without ABS, Special Edition, Canada: LX without ABS, EX

*6 : U.S.: DX and LX with ABS, EX, Canada: LX with ABS, Special Edition, EX-R