

Specifications

Dimensions

Length	4,450 mm (175.2 in)
Width	1,700 mm (66.9 in)
Height	1,390 mm (54.7 in)
Wheelbase	2,620 mm (103.1 in)
Track	1,475 mm (58.1 in)
Front	
Rear	1,475 mm (58.1 in)

Weights

Gross vehicle weight rating	See the certification label attached to the driver's doorjamb.
-----------------------------	--

Engine

Type	Water cooled 4-stroke SOHC* ¹ , SOHC VTEC* ² 4-cylinder gasoline engine
Bore x Stroke	75.0 x 90.0 mm (2.95 x 3.54 in)
Displacement	1,590 cm ³ (97.0 cu-in)
Compression ratio	9.4 : 1* ¹ 9.6 : 1* ²
Spark plugs	See spark plug maintenance section page 145

* 1 : U.S. : DX, LX, Canada: LX, EX

* 2 : U.S. : EX

Capacities

Fuel tank		Approx. 45 l (11.9 US gal , 9.9 Imp gal)
Engine coolant	Change* ¹	
	Manual	3.1 l (0.82 US gal , 0.68 Imp gal)
	Automatic	3.0 l (0.79 US gal , 0.66 Imp gal)* ² 3.2 l (0.85 US gal , 0.70 Imp gal)* ³
	Total	
	Manual	4.2 l (1.11 US gal , 0.92 Imp gal)
	Automatic	4.1 l (1.08 US gal , 0.90 Imp gal)* ² 4.3 l (1.14 US gal , 0.95 Imp gal)* ³
Engine oil	Change* ⁴	
	Including filter	3.3 l (3.5 US qt , 2.9 Imp qt)* ² 3.6 l (3.8 US qt , 3.2 Imp qt)* ³
	Without filter	3.0 l (3.2 US qt , 2.6 Imp qt)* ² 3.3 l (3.5 US qt , 2.9 Imp qt)* ³
	Total	4.0 l (4.2 US qt , 3.5 Imp qt)
Manual transmission fluid	Change	1.8 l (1.9 US qt , 1.6 Imp qt)
	Total	1.9 l (2.0 US qt , 1.7 Imp qt)
Automatic transmission fluid	Change	2.7 l (2.9 US qt , 2.4 Imp qt)
	Total	5.9 l (6.2 US qt , 5.2 Imp qt)
Windshield washer reservoir	U.S. Cars	2.5 l (2.6 US qt , 2.2 Imp qt)
	Canada Cars	4.5 l (4.8 US qt , 4.0 Imp qt)

* 1 : Including the coolant in the reserve tank and that remaining in the engine.

Reserve tank capacity: 0.4 l (0.11 US gal , 0.09 Imp gal)

* 2 : U.S.: DX, LX, Canada: LX, EX

* 3 : U.S.: EX

* 4 : Excluding the oil remaining in the engine.

Air Conditioning

Refrigerant type	HFC-134a (R-134a)
Charge quantity	600 – 650 g (21.2 – 22.9 oz)
Lubricant type	SP-10

Lights

Headlights (H/L/O)	12 V	60/55 W (HB2)
Front turn signal/side marker/ parking lights	12 V –	43/3 CP (SAE 3496) (12 V – 27/8 W)
Rear turn signal lights	12 V –	21 W
Stop/Taillights/Rear side marker lights	12 V –	21/5 W
Back-up lights	12 V	21 W
High-mount brake light	12 V –	21 W
License plate lights	12 V –	3 CP
Interior light	12 V –	5 W *1 12 V – 8 W *2
Trunk light	12 V –	3.4 W

* 1 : Without moonroof

*2 : With moonroof

Battery

Capacity	12 V –	36 AH/5 HR 12 V – 38 AH/5 HR 12 V 47 AH/20 HR
----------	--------	---

Fuses

Interior	See page 196 or the fuse label attached to the inside of the fuse box door under the dashboard.
Under-hood	See page 197 or the fuse box cover.

Alignment

Toe-in	Front	1.0 mm (0.04 in)
	Rear	2.0 mm (0.08 in)
Camber	Front	0°
	Rear	– 1°
Caster	Front	1°40'

Tires

Size	Front/Rear	P185/65R14 85S
	Spare	T105/80D13 82M *1 T105/70D14 83M *2 T125/70D14 93M *3
	Pressure	210 kPa (2.1 kgf/cm ² , 30 psi)
	Pressure	200 kPa (2.0 kgf/cm ² , 29 psi)
	Spare	420 kPa (4.2 kgf/cm ² , 60 psi)

* 1 : U.S.: DX, LX, Canada: LX without ABS

* 2 : Canada: EX without ABS

*3 : U.S.: EX, Canada: LX with ABS, EX with ABS