

Air Conditioning

Refrigerant type	HFC-134a (R-134a)
Charge quantity	500–550 g (17.6–19.4 oz)
Lubricant type	SP-10

Lights

Headlights (H/L/O)	12 V 60/55 W (HB2)
Front turn signal/ Side marker lights	12 V — 43/3 CP (SAE 3496)
Auxiliary lights	12 V — 45 CP (SAE 3497)
Rear turn signal lights	12 V — 32 CP (SAE 1156)
Stop/Taillights	12 V — 32/2 CP (SAE 2057)
Rear side marker lights	12 V — 3 CP (SAE 168)
Back-up lights	12 V — 32 CP (SAE 1156)
License plate lights	12 V — 8 W
Interior light	12 V — 5 W
Trunk light	12 V — 3.4 W

Battery

Capacity	12 V — 36 AH/5 HR
----------	-------------------

Fuses

Interior	See page 192 or the fuse label attached to the inside of the fuse box door under the dashboard.
Underhood	See page 193 or the fuse box cover.

Alignment

Toe-in	Front	0.0 mm (0.00 in)
	Rear	2.0 mm (0.08 in)
Camber	Front	– 15' 20'*
	Rear	– 30'
Caster	Front	1°10'

* : VTEC

Tires

Size	Front/Rear	P175/70R13 82S *1 P185/60R14 82H *2 P195/60R14 85V *3
	Spare	T105/80D13 *1*2 T135/70D15 *3*4
Pressure	Front	220 kPa (2.2 kg/cm ² , 32 psi) *1
		200 kPa (2.0 kg/cm ² , 29 psi) *2*3
	Rear	220 kPa (2.2 kg/cm ² , 32 psi) *1
		200 kPa (2.0 kg/cm ² , 29 psi) *2*3
	Spare	415 kPa (4.15 kg/cm ² , 60 psi)

* 3 : VTEC

* 4 : U.S. : S, Si without ABS, Canada : Si

* 5 : VTEC, U.S. Si with ABS