

Air Conditioning

Refrigerant type	HFC-134a (R-134a)
Charge quantity	600 – 650 g (21.2 – 22.9 oz)
Lubricant type	SP-10

Lights

Headlights (H/LO)	12 V – 60/55 W (HB2)
Front turn signal/side marker/ parking lights	12 V – 43/3 CP (SAE 3497)
Rear turn signal lights	12 V – 21 W
Stop/Taillights	12 V – 21/5 W
Taillights	12 V – 3 CP
Rear side marker lights	12 V – 3 CP
Back-up lights	12 V – 21 W
High-mount brake light	12 V – 21 CP
License plate lights	12 V – 3 CP
Interior light	12 V – 5 W

Battery

Capacity	12 V – 47 AH/20 HR
----------	--------------------

Fuses

Interior	See page 180 or the fuse label attached to the inside of the fuse box door under the dashboard.
Under-hood	See page 181 or the fuse box cover.

Alignment

Toe-in	Front	1.0 mm (0.04 in)
	Rear	2.0 mm (0.08 in)
Camber	Front	0°
	Rear	– 1°
Caster	Front	1°40'

Tires

Size	Front/Rear	P185/65R14 85S
	Spare	T105/80D13 T115/70D14 *
Pressure	Front	210 kPa (2.1 kgf/cm ² , 30 psi)
	Rear	200 kPa (2.0 kgf/cm ² , 29 psi)
	Spare	420 kPa (4.2 kgf/cm ² , 60 psi)

* : For cars with ABS