

Front Suspension

Independent wishbone arms, torsion bar springs with stabilizer bar.

Front Wheel Alignment

Toe-in	0 ± 0.08 in. (2 mm)
Camber	$0' \pm 30'$
Caster	$2^{\circ}10' \pm 45'$

Rear Suspension

Four links, coil springs, with stabilizer bar.

Steering

Recirculating ball.

Service Brake

Hydraulic front and rear ventilated disc brake.

Parking Brake

Mechanical, drum in disc, duo-servo, manual-adjusting, operating on rear wheels.

Battery

Type	75D26R	80D26R	95D31R
Voltage (V)	12	12	12
Cold-cranking performance (Amp)	490	582	622
Reserve capacity (Min.)	123	133	159
BCI group no.	24	24	27

Rear Axle

Gear ratio	4.3:1
Lubricant capacity	3.2 U.S. quarts (3.0 liters)

Front Axle

Gear ratio	4.3:1
Lubricant capacity	1.5 U.S. quarts (1.4 liters)

Shift-on-the-Fly System



Lubricant capacity	0.13 U.S. quarts (0.12 liters)
--------------------	--------------------------------

Wheels and Tires

Tire size	245/70R16
Wheel size	16 x 7JJ
Tire pressure	
Front psi (kPa)	30 (210)
Rear psi (kPa)	35 (240)
Wheel nut tightening torque	87 lb·ft (118 N·m)

Fuses

Fuse boxes are installed on the left side of the instrument panel and the right side of the engine compartment. Each fuse box contains spare fuse cartridges.



NOTICE

Replacing a fuse with one that has a higher rating greatly increases the chances of damaging the electrical system. If you do not have a replacement fuse with the proper rating for the circuit, install one with a lower rating.

Fuse Box: Instrument Panel

Amperage		Applicability
C-1	10A	Starter relay
C-2	15A	Seat heater
C-3	15A	Turn signal light, back-up light
C-4	10A	Rear window and mirror defoggers, cruise control
C-5	15A	Front wiper, washer
C-6	10A	Rear wiper, washer
C-7	–	–
C-8	15A	Engine
C-9	15A	Ignition coil
C-10	10A	Gauges, indicators
C-11	10A	Audio, mirrors, multimeter
C-12	20A	Cigarette lighter
C-13	10A	Anti-theft
C-14	15A	Stop light, high-mount stop light, A/T electronic control unit

C-15	20A	Audio [B]
C-16	10A	Clock [B], interior lights
C-17	25A	Rear defogger
C-18	20A	Door locks, power windows
C-19	25A	Blower
C-20	10A	Air conditioning
C-21	10A	SRS
Circuit breaker 30A		Power window, sunroof, power seat

SRS: Supplemental Restraint System

Fuse Box: Engine Compartment

Amperage		Applicability		
F-1	–	–		
F-2	20A	O ₂ Sensor heater		
F-3	15A	Horn, hazard		
F-4	15A	Headlight, left		
F-5	15A	Headlight, right		
F-6	–	–		
F-7	–	–		
F-8	15A	Front fog light		
F-9	20A	Antilock brake system		
F-10	15A	Fuel pump		
F-11	–	–		
F-12	15A	Tail		
Fusible link wire		FL-1	80A	Main
		FL-2	50A	Key switch
		FL-3	30A	ECM
		FL-4	–	–
		FL-5	–	–
		FL-6	40A	ABS

Light Bulbs

Application	Bulb No.	Quantity	Rating Wattage/ Amperage
Front Lights			
Headlight – halogen	9004	2	65/45 W
Turn signal	1157	2	27 W
Sidemarkers	194	2	3.8 W
Cornering light and parking light	1156	2	27/8 W
Fog light	–	2	55W
Rear Lights			
Back-up	1156	2	27 W
License	–	1	5 W
Stop, Tail and Sidemarkers	1157	2	27/8 W
Turn signal	1156	2	27 W
Interior Illumination			
A/C Bezel	74	2	150 mA
Dome light	–	1	10 W
Map light	–	2	5 W
Luggage compartment light	–	1	8 W
Courtesy light	194	4	3.8 W
Glove box	–	1	1.2 W
Ashtray	74	1	1.4 W
Meter	194	4	3.4 W

Interior Illumination (cont'd)			
A/T Shift indicator	74	1	1.4 W
A/T Driving mode switch	—	2	50 mA
Main cruise control switch	—	1	50 mA
Light switch	—	1	50 mA
Illumination control	—	1	50 mA
Front fog light	—	1	50 mA
Front wiper/washer	—	1	50 mA
Hazard warning flasher	—	1	50 mA
Lighter	—	1	1.4 W
Exterior mirror switch	—	2	0.94 W
Rear wiper/washer	—	1	60 mA
Rear window defogger	—	1	50 mA
Seat heater, driver	—	1	50 mA
Seat heater, passenger	—	1	50 mA
Headlight wiper/washer	—	1	50 mA
Warning Light and Indicators			
A/T Oil temperature	74	1	1.4 W
Turn signal	74	2	1.4 W
Upshift	74	1	1.4 W

High beam	74	1	1.4 W
Antilock brake system	74	1	1.4 W
Airbag	80	1	2 W
Seat belt reminder	80	1	2 W
Check engine	74	1	1.4 W
Low fuel	74	1	1.4 W
4WD	74	1	1.4 W
Oil pressure	74	1	1.4 W
Brake system	74	1	1.4 W
Charging system	74	1	1.4 W
Cruise set	74	1	0.84 W
Cruise main	74	1	0.84 W
Check automatic transmission	—	1	3 W
TOD indicator	74	4	1.4 W
TOD check indicator	74	1	1.4 W
TOD auto indicator	74	1	1.4 W
Winter drive	74	1	1.4 W
Power drive	74	1	1.4 W
Anti-theft	—	1	3 W
A/C switch	80	1	60 mA
Exterior mirror defogger	—	1	0.94 W
Rear window defogger	—	1	60 mA
			80 mA (with timer)
Front fog light	—	1	60 mA
A/T Shift indicator light	—	7	0.91 W

Dimensions and Weights

Wheelbase	108.7 in. (2,760 mm)
Overall Length	183.5 in. (4,660 mm)
Overall Width	72.2 in. (1,835 mm)
Overall Height (At curb wt.)	72.2 in. (1,835 mm)
Tread Front	59.6 in. (1,515 mm)
Tread Rear	59.8 in. (1,520 mm)
GVWR	5,510 lb (2,499 kg)

Note: GVWR—Gross Vehicle Weight Rating