


Identification Numbers

Your car has several identifying numbers located in various places.

The Vehicle Identification Number (VIN) is the 17-digit number your Acura dealer uses to register your car for warranty purposes. It is also necessary for licensing and insuring your car. The easiest place to find the VIN is on a plate fastened to the top of the dashboard. You can see it by looking through the windshield on the driver's side. It is also on the Certification label attached to the driver's doorjamb, and is stamped on the engine compartment bulkhead. The VIN is also provided in bar code on the Certification label.



2.5 TL


The Engine Number is stamped into the engine block. It is on the rear.

3.2 TL


The Engine Number is stamped into the engine block. It is on the front left, below the valve cover.

The Transmission Number is on a label on top of the transmission.

2.5 TL



3.2 TL



Specifications (2.5 TL)

Dimensions

Length	4,865 mm (191.5 in)
Width	1,785 mm (70.3 in)
Height	1,405 mm (55.3 in)
Wheelbase	2,840 mm (111.8 in)
Track	Front 1,520 mm (59.8 in)
	Rear 1,510 mm (59.4 in)

Weights

Gross vehicle weight rating	See the certification label attached to the driver's doorjamb.
-----------------------------	--

Air Conditioning

Refrigerant type	HFC-134a (R-134a)
Charge quantity	700–750 g (24.7–26.5 oz)
Lubricant type	ND-OIL8

Capacities

Fuel tank		Approx. 65 ℓ (17.2 US gal , 14.3 Imp gal)
Engine	Change* ¹	5.2 ℓ (1.37 US gal , 1.14 Imp gal)
coolant	Total	7.0 ℓ (1.85 US gal , 1.54 Imp gal)
Engine oil	Change** ²	
	Including filter	4.3 ℓ (4.5 US qt , 3.8 Imp qt)
	Without filter	4.0 ℓ (4.2 US qt , 3.5 Imp qt)
	Total	5.2 ℓ (5.5 US qt , 4.6 Imp qt)
Automatic	Change	2.7 ℓ (2.9 US qt , 2.4 Imp qt)
transmission	Total	7.2 ℓ (7.6 US qt , 6.3 Imp qt)
fluid		
Differential	Change	0.95 ℓ (1.00 US qt , 0.84 Imp qt)
oil	Total	1.05 ℓ (1.11 US qt , 0.92 Imp qt)
Windshield	US Cars	2.5 ℓ (2.6 US qt , 2.2 Imp qt)
washer	Canada Cars	4.5 ℓ (4.8 US qt , 4.0 Imp qt)
reservoir		

★ 1: Including the coolant in the reserve tank and that remaining in the engine.

Reserve tank capacity:
0.7 l (0.18 US gal , 0.15 Imp gal)

★ 2: Excluding the oil remaining in the engine.

Specifications (2.5 TL)

Lights

Headlights	12 V — 60/55 W (HB2)
Front turn signal lights	12 V — 21 W
Front parking lights	12 V — 5 W
Rear turn signal lights	12 V — 21 W
Stop/Taillights	12 V — 21/5 W
Front fog lights	12 V — 55 W
High mount brake light	12 V — 21 W
Front side marker lights	12 V — 3 CP
Rear side marker lights	12 V — 3 CP
Back-up lights	12 V — 21 W
License plate lights	12 V — 8 W
Interior lights Front	12 V — 5 W
Center	12 V — 8 W
Trunk light	12 V — 5 W
Door courtesy lights	12 V — 3.4 W
Vanity mirror light	12 V — 2 W

Battery

Capacity	12 V — 52 AH/5 HR
----------	-------------------

Fuses

Interior	See page 227 or the fuse label attached to the inside of the fuse box door under the dashboard.
Under-hood	See page 226 or the fuse box cover.

Engine

Type	Water cooled 4-stroke SOHC 5-cylinder gasoline engine
Bore x Stroke	85.0 x 86.4 mm (3.35 x 3.40 in)
Displacement	2,451 cm ³ (150 cu-in)
Compression ratio	9.6 : 1
Spark plugs	See spark plug maintenance section page 166.

Alignment

Toe-in	Front	0.0 mm (0.00 in)
	Rear	2.0 mm (0.08 in)
Camber	Front	0°
	Rear	-0°30'
Caster	Front	2°07'

Tires

Size	Front/Rear	205/60R15 91H
	Spare	T135/70D15
Pressure	Front	210 kPa (2.1 kg/cm ² , 30 psi)
	Rear	200 kPa (2.0 kg/cm ² , 29 psi)
	Spare	420 kPa (4.2 kg/cm ² , 60 psi)