

Gas Station Information

Gasoline:

Premium UNLEADED gasoline
Pump octane of 91 or higher

Gas Tank Capacity:

65 l (17.2 US gal, 14.3 Imp gal)

Recommended Engine Oil:

API SG grade
"Energy Conserving II" oil
SAE 5W-30 viscosity

Engine Oil Capacity:

including filter
4.3 l (4.5 US qt, 3.8 Imp qt)
without filter
4.0 l (4.2 US qt, 3.5 Imp qt)

Tire Pressure (measured cold):

Front: 205 kPa (30 psi)
Rear: 195 kPa (28 psi)

Spare Tire Pressure:

415 kPa (60 psi)

Tire Size (Front and Rear):

205/60R15 89H

Spare Tire: T135/90D15

Other Tire Information:

See label on the passenger's door
jamb

5 Speed Transmission Oil:

SAE 10W-30 or 10W-40 viscosity
API SF or SG grade recommended

Capacity:

1.8 l (1.9 US qt, 1.6 Imp qt)

Automatic Transmission Fluid:

Honda Premium Formula Automatic
Transmission Fluid or an equivalent
DEXRON® II type Automatic Trans-
mission Fluid (ATF)

Capacity:

2.5 l (2.6 US qt, 2.2 Imp qt)

Differential Oil:

Hypoid gear oil classified GL4 or
GL5

Viscosity

SAE 90: above 0°F (— 18°C)

SAE 80W90: below 0°F (— 18°C)

Capacity:

0.9 l (1.0 US qt, 0.8 Imp qt)