



Specifications

Dimensions

Length	188.8 in (4,795 mm)
Width	70.3 in (1,785 mm)
Height	56.9 in (1,445 mm) 57.3 in (1,455 mm) *
Wheelbase	106.9 in (2,715 mm)
Track	Front 61.2 in (1,555 mm) Rear 60.4 in (1,535 mm)

* : 6-cylinder models

Weights

Gross vehicle weight rating	See the certification label attached to the driver's doorjamb.
-----------------------------	--

Air Conditioning

Refrigerant type	HFC-134a (R-134a)
Charge quantity	25–27 oz (700–750 g) 16–18 oz (450–500 g)*
Lubricant type	ND-OIL8

* : 6-cylinder models

Capacities

Fuel tank	Approx. 17.12 US gal (64.8 ℓ, 14.26 Imp gal)
-----------	---

Capacities

Engine coolant	Change* ¹	
	Manual	1.45 US gal (5.5 ℓ, 1.21 Imp gal)
	Automatic	1.43 US gal (5.4 ℓ, 1.19 Imp gal)
	Total	1.48 US gal (5.6 ℓ, 1.23 Imp gal) * ³
Engine oil	Manual	1.85 US gal (7.0 ℓ, 1.54 Imp gal)
	Automatic	1.82 US gal (6.9 ℓ, 1.52 Imp gal)
	Total	1.98 US gal (7.5 ℓ, 1.65 Imp gal) * ³
	Change* ²	
	Including filter	4.5 US qt (4.3 ℓ, 3.8 Imp qt)
	Without filter	4.6 US qt (4.4 ℓ, 3.9 Imp qt) * ³
	Total	4.2 US qt (4.0 ℓ, 3.5 Imp qt)
Manual trans- mission oil	Change	5.9 US qt (5.6 ℓ, 4.9 Imp qt)
	Total	5.3 US qt (5.0 ℓ, 4.4 Imp qt) * ³
Automatic transmission fluid	Change	2.0 US qt (1.9 ℓ, 1.7 Imp qt)
	Change	2.1 US qt (2.0 ℓ, 1.8 Imp qt)
	Total	2.6 US qt (2.5 ℓ, 2.2 Imp qt)
Windshield washer reservoir	Change	3.1 US qt (2.9 ℓ, 2.6 Imp qt) * ³
	Total	6.4 US qt (6.1 ℓ, 5.4 Imp qt)
	Total	7.6 US qt (7.2 ℓ, 6.3 Imp qt) * ³
	U.S. Cars	6.4 US qt (6.1 ℓ, 5.4 Imp qt)
	Canada Cars	7.6 US qt (7.2 ℓ, 6.3 Imp qt)

* 1 : Including the coolant in the reserve tank and that remaining in the engine.

Reserve tank capacity: 0.16 US gal (0.6 ℓ, 0.13 Imp gal)

* 2 : Excluding the oil remaining in the engine.

* 3 : 6-cylinder models



Specifications

Lights

Headlights	High	12 V — 60 W (HB3)
	Low	12 V — 51 W (HB4)
Front turn signal/side marker lights		12 V — 24/2.2 CP
Front parking lights		12 V — 3 CP
Rear turn signal lights		12 V — 21 W
Stop/Taillights		12 V — 21/5 W
Taillight		12 V — 3 CP
High-mount brake light		12 V — 21 W
Back-up lights		12 V — 21 W
License plate lights		12 V — 3 CP
Ceiling light		12 V — 7 W
Trunk lights		12 V — 5 W
Door courtesy lights		12 V — 2 CP
Vanity mirror light		12 V — 1.8 W

Battery

Capacity	4-cylinder	12 V — 52 AH/5 HR
	6-cylinder	12 V — 55 AH/5 HR

Fuses

Interior	See page 335 or the fuse label attached to the inside of the fuse box door on each side of the dashboard.
Under-hood	See page 334 or the fuse box cover.

Engine

Type	Water cooled 4-stroke SOHC, SOHC VTEC 4-cylinder, SOHC 6-cylinder (V6), gasoline engine
Bore x Stroke	3.39 x 3.82 in (86.0 x 97.0 mm) 3.39 x 3.39 in (86.0 x 86.0 mm) ^{*3}
Displacement	137.5 cu-in (2,254 cm ³) 182.8 cu-in (2,997 cm ³) ^{*3}
Compression ratio	8.8 : 1 ^{*1} 9.3 : 1 ^{*2} 9.4 : 1 ^{*3}
Spark plugs	See spark plug maintenance section pages 273 and 275.

* 1 : DX, Value Package

* 2 : LX, EX, SE

* 3 : 6-cylinder models

Alignment

Toe-in	Front	0.00 in (0.0 mm)
	Rear	0.08 in (2.0 mm)
Camber	Front	0°
	Rear	-0°30'
Caster	Front	3°00'

CONTINUED



Specifications

Tires

Size	Front/Rear	P195/70R14 90S ^{*1} P195/65R15 89H ^{*2} P205/65R15 92V ^{*4}
	Spare	T125/70D15 ^{*3} T135/90D15 ^{*4}
Pressure	Front/Rear	29 psi (200 kPa , 2.0 kgf/cm ²) ^{*1} 30 psi (210 kPa , 2.1 kgf/cm ²) ^{*2 *4}
	Spare	60 psi (420 kPa , 4.2 kgf/cm ²)

* 1 : DX, Value Package

* 2 : LX, EX, SE

* 3 : 4-cylinder models

* 4 : 6-cylinder models