

Gas Station Information

Gasoline:

Premium UNLEADED gasoline
Pump octane of 91 or higher

Gas Tank Capacity:

18.5 US gal. (70 l)

Recommended Engine Oil:

API SG grade "Energy Conserving
II" oil
SAE 10W—30 viscosity
For temperatures below 32° F (0°C)
Use SAE 5W—30

Engine Oil Capacity:

including filter 5.3 US qt. (5.0 l)
without filter 4.5 qt. (4.3 l)

Tire Pressure (measured cold):

Front: 33 psi (2.3 kg/cm², 230 kPa)
Rear: 40 psi (2.8 kg/cm², 275 kPa)

Folding Spare Tire Pressure:

If used as a spare for either
front tires:
26 psi (1.8 kg/cm², 180 kPa)
rear tires:
32 psi (2.2 kg/cm², 220 kPa)

Tire Size:

Front: 205/50ZR15
Rear: 225/50ZR16
Folding Spare Tire: 165/80D15

Other Tire Information:

See label on the drivers door jamb

5 Speed Transmission Oil:

SAE 10W—30 or 10W—40 viscosity
API SF or SG grade recommended

Capacity (including differential):

2.9 US qt (2.7 l)

Automatic Transmission Fluid:

Honda Premium Formula Automatic
Transmission Fluid or an equivalent
DEXRON® II type Automatic Trans-
mission Fluid (ATF)

Capacity (including differential):

3.1 US qt. (2.9 l)