

Specifications

Dimensions

Length		155.0 in (3,938 mm)
Width		66.7 in (1,695 mm)
Height		53.3 in (1,355 mm)
Wheelbase		94.5 in (2,400 mm)
Track	Front	56.5 in (1,435 mm)
	Rear	52.2 in (1,325 mm)

Weights

Gross vehicle weight rating	See the certification label attached to the driver's doorjamb.
-----------------------------	--

Engine

Type		Water cooled 4-stroke SOHC VTEC in line 3-cylinder gasoline engine
Bore x Stroke		2.8 x 3.21 in (72 x 81.5 mm)
Displacement		60.8 cu-in (995 cm ³)
Compression ratio	M/T	10.8 : 1
	CVT	10.3 : 1
Spark plugs ^{*1}		ILZFR5A-11

* 1 : Contact your Honda dealer when replacement is necessary.

Capacities

Fuel tank		Approx. 10.6 US gal (40 ℓ , 8.8 Imp gal)
Engine coolant	Change ^{*2}	0.61 US gal (2.3 ℓ , 0.51 Imp gal)
	Total	1.06 US gal (4.0 ℓ , 0.88 Imp gal)
Engine oil	Change	
	Including filter	2.6 US qt (2.5 ℓ , 2.2 Imp qt)
	Without filter	2.4 US qt (2.3 ℓ , 2.0 Imp qt)
	Total	3.2 US qt (3.0 ℓ , 2.6 Imp qt)
Manual transmission fluid	Change	1.6 US qt (1.5 ℓ , 1.3 Imp qt)
	Total	1.7 US qt (1.6 ℓ , 1.4 Imp qt)
Automatic transmission fluid (CVT) ^{*3}	Change	3.5 US qt (3.3 ℓ , 2.9 Imp qt)
	Total	5.8 US qt (5.5 ℓ , 4.8 Imp qt)
Windshield washer reservoir		4.8 US qt (4.5 ℓ , 4.0 Imp qt)

* 2 : Including the coolant in the reserve tank and that remaining in the engine.

Reserve tank capacity: 0.11 US gal (0.4 ℓ , 0.09 Imp gal)

* 3 : U.S. model

Air Conditioning

Refrigerant type	HFC-134a (R-134a)
Charge quantity	17.6 – 19.4 oz (500 – 550 g)
Lubricant type	SP-10

Lights

Headlights (HI/LO)	12 V – 60/55 W (HB2)
Front turn signal lights	12 V – 21 W
Front parking lights	12 V – 5 W
Side marker lights	12 V – 5 W
Rear turn signal lights	12 V – 21 W
Stop/Taillights	12 V – 21/5 W
Back-up lights	12 V – 18 W
Trunk light	12 V – 3.4 W
License plate light	12 V – 5 W
Interior light	12 V – 5 W

Battery

Capacity	M/T	12 V – 27 Ah/5 HR
	CVT*	12 V – 30 Ah/5 HR

Fuses

Interior	See page 234 or the fuse label attached to the inside of the fuse box door under the dashboard.
Under-hood	See page 235 or the fuse box cover.

* U.S. model

Alignment

Toe-in	Front	0.00 in (0.0 mm)
	Rear	0.12 in (3.0 mm)
Camber	Front	0°
	Rear	– 1°
Caster	Front	2°

Tires

Size	Front/Rear	P165/65R14 78S
	Spare	T115/70D14 88M
Pressure	Front	38 psi (260 kPa)
	Rear	35 psi (240 kPa)
	Spare	60 psi (420 kPa)