

## Service Information Summary

---

### **Gasoline:**

Premium unleaded gasoline, pump octane number of 91 or higher.

### **Fuel Tank Capacity:**

17.09 US gal (64.7 ℓ)

### **Recommended Engine Oil:**

API Service SJ "Energy Conserving" oil, SAE 5W-20 viscosity (see page [204](#)).

Oil change capacity (including filter):

4.5 US qt (4.3 ℓ)

### **Automatic Transmission Fluid:**

Honda ATF-Z1 (Automatic Transmission Fluid) preferred, or a DEXRON® III ATF as a temporary replacement (see page [209](#)).

### **Manual Transmission Fluid:**

Honda Manual Transmission Fluid preferred, or an SAE 10W-30 or 10W-40 motor oil as a temporary replacement (see page [210](#)).

Capacity:

2.6 US qt (2.5 ℓ)

### **Power Steering Fluid:**

Honda Power Steering Fluid preferred, or another brand of power steering fluid as a temporary replacement. Do not use ATF (see page [212](#)).

### **Brake Fluid:**

Honda Heavy Duty Brake Fluid DOT 3 preferred, or a DOT 3 or DOT 4 brake fluid as a temporary replacement (see page [211](#)).

### **Tire Pressure (measured cold):**

Manual Transmission Models

Front:

35 psi (240 kPa, 2.4 kgf/cm<sup>2</sup>)

Rear:

32 psi (220 kPa, 2.2 kgf/cm<sup>2</sup>)

Automatic Transmission Models

Front:

32 psi (220 kPa, 2.2 kgf/cm<sup>2</sup>)

Rear:

32 psi (220 kPa, 2.2 kgf/cm<sup>2</sup>)

### **Spare Tire Pressure:**

60 psi (420 kPa, 4.2 kgf/cm<sup>2</sup>)