

# Specifications

## Dimensions

Length	4,395 mm (173.0 in)	
Width	1,700 mm (66.9 in)	
Height	1,370 mm (53.9 in)	
Wheelbase	2,620 mm (103.1 in)	
Track	Front	1,475 mm (58.1 in)
	Rear	1,465 mm (57.7 in)

## Weights

Gross vehicle weight rating	See the certification label attached to the driver's door jamb.
-----------------------------	---

## Engine

Type	Water cooled 4-stroke SOHC 4-cylinder gasoline engine
Bore x Stroke	75.0 x 84.5 mm (2.95 x 3.33 in) <sup>*1</sup> 75.0 x 90.0 mm (2.95 x 3.54 in) <sup>*2</sup>
Displacement	1,493 cm <sup>3</sup> (91.1 cu-in) <sup>*1</sup> 1,590 cm <sup>3</sup> (97.0 cu-in) <sup>*2</sup>
Compression ratio	9.2 : 1
Spark plugs	See spark plug maintenance section page 136 .

\* 1 : US: DX, LX, Canada: LX, EX

\* 2 : US: EX, Canada: EX-V

## Capacities

Fuel tank		Approx. 45 ℓ (11.9 US gal , 9.9 Imp gal)
Engine coolant	Change <sup>*1</sup>	
	Manual	3.6 ℓ (0.95 US gal , 0.79 Imp gal)
	Automatic	3.5 ℓ (0.92 US gal , 0.77 Imp gal) <sup>*2</sup>
	Total	3.8 ℓ (1.00 US gal , 0.84 Imp gal) <sup>*3</sup>
	Manual	4.5 ℓ (1.19 US gal , 0.99 Imp gal)
	Automatic	4.4 ℓ (1.16 US gal , 0.97 Imp gal) <sup>*2</sup>
	Total	4.7 ℓ (1.24 US gal , 1.03 Imp gal) <sup>*3</sup>
Engine oil	Change <sup>*4</sup>	
	Including filter	3.3 ℓ (3.5 US qt , 2.9 Imp qt)
	Without filter	3.0 ℓ (3.2 US qt , 2.6 Imp qt)
	Total	4.0 ℓ (4.2 US qt , 3.5 Imp qt)
Manual trans- mission oil	Change	1.8 ℓ (1.9 US qt , 1.6 Imp qt)
	Total	1.9 ℓ (2.0 US qt , 1.7 Imp qt)
Automatic trans- mission fluid	Change	2.7 ℓ (2.9 US qt , 2.4 Imp qt)
	Total	5.9 ℓ (6.2 US qt , 5.2 Imp qt)
Windshield washer reservoir	US Cars	2.5 ℓ (2.6 US qt , 2.2 Imp qt)
	Canadian Cars	4.5 ℓ (4.8 US qt , 4.0 Imp qt)

\* 1 : Including the coolant in the reserve tank and that remaining in the engine.

Reserve tank capacity:

0.4 ℓ (0.11 US gal , 0.09 Imp gal)

\* 2 : US: DX, LX, Canada: LX, EX

\* 3 : US: EX, Canada: EX-V

\* 4 : Excluding the oil remaining in the engine.

# Specifications

## Lights

Headlights (H/L/O)	12 V — 60/55 W
Front turn signal/ side marker lights	12 V — 43/3 CP (SAE 3497)
Rear turn signal lights	12 V — 32 CP (SAE 1156)
Stop/Taillights	12 V — 32/2 CP (SAE 2057)
Rear side marker lights	12 V — 3 CP (SAE 168)
Back-up lights	12 V — 32 CP (SAE 1156)
High mount brake light	12 V — 32 CP
License plate lights	12 V — 8 W
Interior light	12 V — 8 W
Trunk light	12 V — 3.4 W

## Battery

Capacity	12 V — 38 AH/5 HR
----------	-------------------

## Fuses

Interior	See the fuse label attached to the inside of the fuse box door under the dashboard.
Underhood	See the fuse box cover.

## Alignment

Toe-in	Front	0.0 mm (0.00 in)
	Rear	2.0 mm (0.08 in)
Camber	Front	0°
	Rear	-20'
Caster	Front	1°10'

## Tires

Size	Front/Rear	P175/70R13 82S *1 P175/65R14 81H *2
	Spare	T105/80D13 *1 T135/70D15 *3 T105/70D14 *4
Pressure	Front/Rear	220 kPa (2.2 kg/cm <sup>2</sup> , 32 psi) *1 200 kPa (2.0 kg/cm <sup>2</sup> , 29 psi) *2
	Spare	415 kPa (4.15 kg/cm <sup>2</sup> , 60 psi)

\* 1 : US: DX, LX, Canada: LX, EX

\* 2 : US: EX, Canada: EX-V

\* 3 : US: EX, Canada: EX-V with ABS

\* 4 : Canada: EX-V without ABS